

Flammable Gas 2 Hazchem Sign

Product Images





Description

Indicates the storage or containment of Class 2 Flammable Gases within a facility, vehicle or container etc.

- Class 2, Division 2.1 Flammable Gas is defined as Gases which, at 20 °C and a standard temperature of 101.3 kPa, are ignitable when in a mixture of 13% or less by volume in air.
- Examples: Acetylene, Natural gas, and Liquified Petroleum Gas (LPG).
- Read Chapter 2.2 of the Australian Dangerous Goods Code for more information (latest edition 7.6)
 available here.
- Recognisable by a red background with black wording, flame symbol and the number '2'.
- Complies with ADG, WHS Regulations and Australian Standard AS1216-2006.
- Available in a large range of materials and sizes to suit any application.
- Hazchem signs are required at any workplace that stores hazardous chemicals over a certain quantity.
- During an emergency situation, this sign will allow emergency services to identify any chemicals present.
- It is important as a business to correctly label all hazardous chemicals using the appropriate Hazchem Signage.

All Bronson Safety Hazchem signage meets the requirements of Australian Government Legislation.

- For more information on Class 2 Flammable Gases, click here.
- For information on Hazchem labelling and signs in a workplace, read WorkSafe Australia's Model Code of Practice view here.
- For all other information, consult the Dangerous Goods Storage and Handling Regulations for your State or Territory click here.

Additional Information

Safety Sign Type

GHS & Hazchem

Product Options

| Sign Size: | 50mm x 50mm |
|----------------|---------------------|
| | 100mm x 100mm |
| | 150mm x 150mm |
| | 200mm x 200mm |
| | 270mm x 270mm |
| Sign Material: | Colorbond Steel |
| | Polypropylene |
| | Self Adhesive Vinyl |