

Tri-Bund Flexible Bunding

Product Images





Description

Tri-Bund Flexible Bunding is today's flexible and cost-effective solution to bunding in traffic areas. Other rigid bunding designs present difficulty for traffic, especially forklifts, and can increase the risk of spills due to the inherent 'bump' factor.

- Caters to all types of traffic, including forklift traffic.
- Returns to original shape almost immediately after it is driven over.
- Simple and quick to install.
- High visibility yellow.
- Effectively prevents spills from progressing into or out of protected areas.
- Made from durable, heavy-duty PVC.
- Easy to clean.
- Available in an ideal 50mm height.
- Fully encased foam prevents mould or deterioration.
- **A4842 PVC Adhesive** is required for joining Tri-Bund sections together.
- **A4841 Polyurethane Adhesive** is required to seal Tri-Bund to the floor (typically one tube per 2 lengths of Tri-bund).
- Tri-Bund Flexible Bunding Dimensions: 50(H) x 110(W) x 2000(L)mm

Products in this set



Body 2000(L) x 110(W) x 50(H)mm Tri-Bund Flexible Bunding



90° Joiner Tri-Bund Flexible Bunding



Floor Adhesive Polyurethane 310gm Tri-Bund Flexible Bunding



PVC Adhesive 250ml Tri-Bund Flexible Bunding